

Building Product Information Requirements

BPIR — Product Information Sheet

Building (Building Product Information Requirements) Regulations 2022

1. Product Details

Series Name	[1200 × 600 Series]
SKUs Covered	[IM612A3-98, IM612A4-98, FTDYQ61201M, FTDR612033, FTDR612031, AHJ61291S, YQ61203M, YQ61207M, YQ61205M, HF-EQ126061Y, 126DJ1569P, 126DJ1018P, 126RJ018M1, 126DJ034P, 126RJ008M1, 126RJ006M1]
Product Type	Porcelain Tile
Intended Use	[Wall / Floor]

2. Manufacturer Information

Manufacturer	[NEWPEARL Group Co., Ltd.]
Address	[Taobo Boulevard Tao Bo Da Dao, Chan Cheng Qu, Fo Shan Shi, Guang Dong Sheng, China]
Website	[https://www.newpearl-global.com/]
Email	[newpearlglobal@newpearl.com]

3. Importer Information

Importer	La Perla Limited
Trading Name	La Perla Limited
NZBN	9429042027713
Address	1/123 Pilkington Road, Panmure, Auckland 1072, New Zealand
Website	https://newpearl.co.nz/
Email	info@laperla.co.nz

4. Relevant Building Code Clauses

NZ Building Code Clause	Description
B2	Durability
E3	Internal Moisture
F2	Hazardous Building Materials

5. Product Performance

Property	Value / Rating
Water Absorption	[$\leq$ 0.5%]
Surface Finish	[Matt/Polished]
Breaking Strength	[$\geq$ 1300 N]
Abrasion Resistance	[PEI 4]
Chemical Resistance	[Class A]
Frost Resistance	[Pass]
Tile Thickness	[9mm / 10mm]
Tile Sizes (this series)	[1200x600mm]

6. Compliance Statement

The product contributes to compliance with the New Zealand Building Code through:

- Low water absorption
- High mechanical strength
- Durable ceramic surface
- Resistance to wear and moisture

Supporting documentation includes:

- ISO 10545 Test Reports
- Technical Data Sheet
- Manufacturer Test Certificates

7. Scope of Use

Suitable for:

- ☒ Residential floors
- ☒ Residential walls
- ☒ Commercial floors
- ☒ Commercial walls
- ☐ Wet areas
- ☒ Internal applications
- ☐ External applications

8. Limitations on Use

This product shall not be:

- Used as a structural building element
- Used in applications beyond manufacturer's recommendations
- Installed on unstable substrates
- Used where a higher slip rating is required without further assessment

9. Design Requirements

The building designer shall ensure:

- Correct tile selection for intended use
- Appropriate slip resistance classification
- Suitable substrate design
- Adequate movement joints

10. Installation Requirements

Installation shall be completed:

- By competent tradespersons
- In accordance with AS 3958
- Using suitable adhesives and grouts
- Following manufacturer's instructions

11. Maintenance Requirements

Routine maintenance includes:

- Cleaning using pH-neutral detergent
- Avoiding harsh acidic cleaners
- Maintaining grout joints
- Replacing damaged tiles where necessary

12. Warning or Ban Statement

This product is not subject to a warning or ban under Section 26 of the Building Act 2004.

◆. Document Control

Field	Value
Document Number	[BPIR-LP1200]
Version	[1.0]
Issue Date	[24 June 2026]
Review Date	[24 June 2027]
Prepared by	La Perla Limited / Newpearl New Zealand Limited